



# UEX15

## PRODUCT DESCRIPTION

This resin grade is the recommended ribbon where durability of the printed image is required. It offers excellent scratch resistance, and is noted for its adaptability and excellent print performance over a wide variety of media. It has been engineered to give maximum performance over a wide range of energy settings, making for easy change with other resin products with little or no printer adjustment required. This resin offers the blackest of prints and maximum scratch resistance. A premium backcoat technology ensures maximum printhead protection extends print head life. This grade can be confidently specified with a wide range of proprietary label brands and on all types of near edge technology printers.

## RECOMMENDED SUBSTRATES

Coated and synthetic papers, polyethylene, polypropylene, polyester



## EXAMPLES OF TYPICAL APPLICATIONS

					
AUTOMOTIVE	OUTDOOR	HEALTHCARE	SHRINK WRAP	GENERAL	AGENCY
					
CIRCUIT BOARD	ASSET TRACKING	ELECTRONIC COMPONENTS	CHEMICAL DRUM	EXTREME ENVIRONMENT	SIGNAGE

# UEX15



## PERFORMANCE CHARACTERISTICS

- > Super Scratch resistance  
Low printhead energy required
- > Ideal choice for general high durability labelling applications
- > Ideal for rating plates, automotive, outdoor, pharmaceutical labels
- > High speed printing up to 12" inches per second
- > ISEGA certification

RIBBON SPECIFICATIONS	
DESCRIPTION	TECHNICAL
BASE FILM CARRIER	4.5 Micron Polyester
TOTAL RIBBON THICKNESS	6.7 Microns
INK TYPE	Resin (Near Edge Technology)
COLOUR	Black
INK MELTING POINT	70-80°C
DENSITY	>1.8

RIBBON STORAGE CONDITIONS	
DESCRIPTION	TECHNICAL
TEMPERATURE	5°C to 35°C (41F to 95F)
HUMIDITY	10% to 85% relative humidity
LIGHT	Avoid direct sunlight

CERTIFICATIONS AND APPROVALS	
DESCRIPTION	TECHNICAL
ISEGA	FDA
EU Food directive	
BRC	
RoHS	
REACH	

This information is the best available on the above ribbon grade. These results should, however, only be regarded as a general guide to material properties and is not a guarantee.



Thermal Transfer Solutions Limited, Unit 2, The IO Centre,  
Nash Road, Park Farm North, Redditch, Worcestershire B98 7AS  
t: 01527 517577 | f: 01527 517533 | e: sales@tts.eu.com  
[www.thermaltransfersolutions.com](http://www.thermaltransfersolutions.com)



0000629

