

# PDX80

## HIGH PERFORMANCE FLAT HEAD WAX RESIN

### PRODUCT DESCRIPTION

This grade is one of the best performing flat head technology wax resin grades on the market and offers an excellent all round high performance for printing dark, crisp images and barcodes on a wide range of paper and synthetic labels, with the durability and smudge/scratch resistance expected of such a premium product.

Developed specifically to cover the widest possible range of synthetic materials and coated papers, this grade offers the highest level of durability and performance from a flat head technology wax resin grade. This grade has been developed to print at low energy levels allowing for higher print speeds. It has also been used very successfully as a replacement grade for the world's leading wax resin grade, Ricoh B110A.

### RECOMMENDED SUBSTRATES

Coated/uncoated paper & tag stocks, synthetic paper, polyethylene, polypropylene, polyolefin, gloss paper, flood-coated paper, UV varnished labels

### PERFORMANCE PROPERTIES

#### PRINT SENSITIVITY

9

#### HEAT RESISTANCE

8

#### ABRASION RESISTANCE

9

#### SOLVENT RESISTANCE

6

#### LABEL ADAPTABILITY

9

LOW

MEDIUM

HIGH

### TYPICAL APPLICATIONS



PHARMACY



SHELVING



LOGISTICS



RETAIL



GENERAL



INVENTORY



PRODUCT ID



RFID



HORTICULTURE

NUMBER  
PLATES

SHIPPING



SIGNAGE



# PDX80

## HIGH PERFORMANCE FLAT HEAD WAX RESIN

### PERFORMANCE CHARACTERISTICS

- High levels of print durability
- Prints on a wide variety of substrates from uncoated papers to mid-range synthetic films
- Dark, dense images for reliable printing
- Prints at high speeds delivering crisp, rotated barcodes
- Dissipates static
- Heat resistant up to 120°C on certain materials
- Features enhanced printer performance
- Meets BS5609 standards with certain label materials
- Excellent replacement grade for Ricoh B110A

### Flat Head Technology Grades\*

<b>EWX10</b>	<b>Premium Wax</b> Best choice for general purpose labelling
<b>GPX10</b>	<b>High Performance Wax</b> General purpose labelling with extra durability
<b>PDX25</b>	<b>Premium Wax Resin</b> Great print performance with very good durability
<b>PDX80</b>	<b>High Performance Wax Resin</b> Great print performance with excellent scratch resistance
<b>SRX10</b>	<b>Premium Resin</b> Extra scratch resistance on synthetic labels
<b>SDX80</b>	<b>Premium Textile Resin</b> Excellent print on textiles with wash resistance

\*These ribbon grades are for use with flat head technology printers. We also offer ribbons grades for near edge technology printers and thermal transfer coders.

PDX80

HIGH PERFORMANCE FLAT HEAD WAX RESIN

RIBBON SPECIFICATIONS	
DESCRIPTION	TECHNICAL
BASE FILM CARRIER	4.5 Micron Polyester
TOTAL RIBBON THICKNESS	6.8 Microns +/- 0.02
INK TYPE	Wax/Resin (flat head technology)
COLOUR	Black
INK MELTING POINT	75°C
DENSITY	1.8

RIBBON STORAGE CONDITIONS	
DESCRIPTION	TECHNICAL
TEMPERATURE	5°C to 35°C (41F to 95F)
HUMIDITY	10% to 85% relative humidity
LIGHT	Avoid direct sunlight

CERTIFICATIONS AND APPROVALS	
DESCRIPTION	TECHNICAL
ISO 9001:2015 & ISO 14001:2015	All ribbons have been manufactured to these international quality standard
RoHs/WEEE	EC directives 2012/19/EU and 2011/65/EU, compliance to the limitation of dangerous substances in electrical and electronics equipment
HEAVY METALS	94/62/EC & 2011/65/EU
TSCA/CP 65	The ribbon does not contain any of the substances on this list
AMES TEST	The ribbon is not mutagenic, does not cause DNA modifications
EC DIRECTIVES	1999/45/EC and 2001/59/EC. This ribbon does not contain any substance classified as dangerous for health
FOOD CONTACT	1935/2004/EC
REACH/SVHC	Does not contain any of the SVHCs listed - 1907 / 2006/EC
DISPOSAL	To be disposed of as mixed industrial waste

This information is the best available on the above ribbon grade. These results should, however, only be regarded as a general guide to material properties and is not a guarantee.



**UK Office**  
**Thermal Transfer Solutions Ltd**  
 Unit 27, Eagle Road  
 Manorside Industrial Estate  
 Redditch, Worcestershire, B98 9HE  
**T:** +44 (0)1527 517577 | **F:** +44 (0)1527 517533  
**E:** sales@tts.eu.com



**Dutch Office**  
**Thermal Transfer Solutions BV**  
 De Factorij 4  
 1689 AL Zwaag  
 The Netherlands  
**T:** +31 (0)229 859 831  
**E:** eusales@tts.eu.com