

# UJEX 35

## COLOURS

### PREMIUM RESIN

#### PRODUCT DESCRIPTION

This grade is an excellent all round premium resin ribbon available in a range of colours, for printing deep, crisp images on a wide variety of synthetic and smooth labels. It offers increased levels of durability and smudge/scratch resistance expected of such a premium product and guarantees the best possible print results on smooth surfaces and polyethylene or polyester materials. With excellent print performance, these colours are suitable for use on all types of **NEAR EDGE** and **FLAT HEAD** technology printers.

#### AVAILABLE COLOURS



#### RECOMMENDED SUBSTRATES

Coated paper and tag materials, synthetic paper, polyethylene, polypropylene, polyolefin, most types of flexible packaging films

#### PERFORMANCE PROPERTIES

##### PRINT SENSITIVITY



##### HEAT RESISTANCE



##### ABRASION RESISTANCE



##### SOLVENT RESISTANCE



##### LABEL ADAPTABILITY



LOW MEDIUM HIGH

#### TYPICAL APPLICATIONS

 AUTOMOTIVE	 OUTDOOR	 HEALTHCARE	 SHRINKWRAP
 GENERAL	 AGENCY	 SIGNAGE	 CHEMICAL DRUM
 ASSET TRACKING	 ELECTRONIC COMPONENTS	 FLEXIBLE PACKAGING	



# UEX35

## COLOURS

### PREMIUM RESIN

#### PERFORMANCE CHARACTERISTICS

- Ideal choice for general high durability labelling applications
- Great for printing onto smooth surfaces
- Provides vivid colour prints with good coverage
- Good scratch and smudge resistance
- Low printhead energy required
- Ideal for rating plates, automotive, outdoor and pharmaceutical labels

#### Technology Grades\*

**NEX11**  
COLOURS

##### Premium Wax Resin

Very versatile for all types of labels and packaging films

**UEX35**  
COLOURS

##### Premium Resin

High scratch and chemical resistance

#### RIBBON SPECIFICATIONS

DESCRIPTION	TECHNICAL
BASE FILM CARRIER	4.5 Micron Polyester
TOTAL RIBBON THICKNESS	7 Microns +/- 0.02
INK TYPE	Resin (near edge technology)
COLOUR	Various
INK MELTING POINT	85°C
DENSITY	Varies (according to colour)

#### RIBBON STORAGE CONDITIONS

DESCRIPTION	TECHNICAL
TEMPERATURE	5°C to 35°C (41F to 95F)
HUMIDITY	10% to 85% relative humidity
LIGHT	Avoid direct sunlight

#### CERTIFICATIONS AND APPROVALS

DESCRIPTION	TECHNICAL
ISO 9001:2015 & ISO 14001:2015	All ribbons have been manufactured to these international quality standard
RoHs/WEEE	EC directives 2012/19/EU and 2011/65/EU, compliance to the limitation of dangerous substances in electrical and electronics equipment
HEAVY METALS	94/62/EC & 2011/65/EU
TSCA/CP 65	The ribbon does not contain any of the substances on this list
AMES TEST	The ribbon is not mutagenic, does not cause DNA modifications
EC DIRECTIVES	1999/45/EC and 2001/59/EC. This ribbon does not contain any substance classified as dangerous for health
FOOD CONTACT	1935/2004/EC
REACH/SVHC	Does not contain any of the SVHCs listed - 1907 / 2006/EC
DISPOSAL	To be disposed of as mixed industrial waste

This information is the best available on the above ribbon grade. These results should, however, only be regarded as a general guide to material properties and is not a guarantee.



#### UK Office

##### Thermal Transfer Solutions Ltd

Unit 27, Eagle Road  
Manorside Industrial Estate  
Redditch, Worcestershire, B98 9HE

T: +44 (0)1527 517577 | F: +44 (0)1527 517533

E: sales@tts.eu.com



#### Dutch Office

##### Thermal Transfer Solutions BV

De Factorij 4  
1689 AL Zwaag  
The Netherlands

T: +31 (0)229 859 831

E: eusales@tts.eu.com